

Serial No.: 10/517,305
Atty. Docket No.: P70298US0

REMARKS

The Office Action mailed May 7, 2007, has been carefully reviewed and Applicant notes with appreciation the identification of allowable subject matter.

By this Amendment, Applicant has amended claims 13 and 19. Claims 13-24 remain pending in the application. Claims 13 and 19 are independent.

The Examiner rejected claims 13-24 under 35 U.S.C. 112, second paragraph, as being indefinite but stated that claims 13-24 would be allowable if rewritten or amended to overcome the rejection under 35 U.S.C. 112, second paragraph.

By this Amendment, claims 13 and 19 have been amended to more particularly point out and distinctly claim the subject matter which Applicant regards as the invention. Specifically, the term "bistatic pair" has been defined in claims 13 and 19 as constituting a receiver and a transmitter that are placed at different points, with each such bistatic pair being defined in the claims as a measuring facility. This meaning of "biostatic" as referring to a transmitter and a receiver at two separated sites is well known in the art, as evidenced by enclosed pages 36-1 and 36-2 of Skolnik's Radar Handbook (McGraw-Hill, Inc., 1970). Accordingly, with this clarification, favorable

Serial No.: 10/517,305
Atty. Docket No.: P70298US0

reconsideration and allowance of claims 13 and 19, as well as claims 14-18 and 20-24 properly dependent thereon, is requested in accordance with the Examiner's indication of allowable subject matter.

With this amendment and the foregoing remarks, it is respectfully submitted that the present application is in condition for allowance. Should the Examiner have any questions or comments, the Examiner is cordially invited to telephone the undersigned attorney so that the present application can receive an early Notice of Allowance.

Respectfully submitted,

JACOBSON HOLMAN PLLC

By *Harvey B. Jacobson, Jr.* *Reg. No. 40,495*
for Harvey B. Jacobson, Jr.
Reg. No. 20,851

400 Seventh Street, NW
Washington, D.C. 20004-2201
Telephone: (202) 638-6666
Date: August 6, 2007
HBJ/SCB

R:\SBAILEY\2007\08-07\P70298US0-AMD

Försvarets civilförvaltning
 Patentenheten
 104 50 Stockholm

Institute of Physics

for Mechanical Engineers

and Statistics with

book

Electrical Engineers
 Control
 Handbook

ics

Handbook
 of
 Scientists and Engineers
 Book
 Designers' Handbook

and Electronic Circuits

Handbook

rical Code

Radar Handbook

EDITOR-IN-CHIEF

MERRILL I. SKOLNIK

Naval Research Laboratory

McGRAW-HILL BOOK COMPANY

New York St. Louis San Francisco Düsseldorf Johannesburg
 Kuala Lumpur London Mexico Montreal New Delhi
 Panama Rio de Janeiro Singapore Sydney Toronto

RADAF HANDI MERRILL I

Superintendent, Radar
Naval Research Labora

The RADAR HANDBOOK volume a comprehensive aspects of radar. Broad each chapter written b his particular specialt; for all those who are ir development, or proci or with research in rad

Some of the chapters provide information. Others are written for those engaged in radar, not just for spectators.

Almost every topic radar is included. The subsystems of which described in chapter receivers, displays, radar, antennas and the handbook are the techniques such as CW, FM-CW, tracking compression, digital radar and synthetic analysis of radar measurement accuracy signal management design and automation. Chapters are devoted ground and sea clutter and target noise.

One of the features of this book is the discussion of selected topics that are included for use as a means of introduction by other chapters. These include marine radar, satellite radar astronomy, the subjects of lasers and electromagnetism, and because of their common interest to many

1536 Pages

RADAR HANDBOOK

Copyright © 1970 by McGraw-Hill, Inc. All Rights Reserved.
Printed in the United States of America. No part of this
publication may be reproduced, stored in a retrieval system,
or transmitted, in any form or by any means, electronic,
mechanical, photocopying, recording, or otherwise, without
the prior written permission of the publisher.
Library of Congress Catalog Card Number 69-13615

07-057908-3

67890 KРБР 798

Chapter 36

Bistatic and Multistatic Radar

JAMES W. CASPERS

Naval Electronics Laboratory Center

36.1 Introduction	36-1
36.2 Bistatic Location Techniques	36-3
36.3 Bistatic Sensitivity, Doppler, and Coverage	36-3
36.4 Multistatic Location Techniques	36-9
36.5 Multistatic Sensitivity, Doppler, and Coverage	36-13
36.6 Bistatic Cross Sections	36-13
36.7 Special Problems	36-14
36.8 Applications	36-16

36.1 INTRODUCTION

Early experimental radar systems in the United States and the United Kingdom were predominantly of the bistatic type, the transmitter and receiver usually being separated by a distance comparable to the target distance.^{1,2} With the invention of the duplexer at U.S. Naval Research Laboratory in 1938, providing a means of using a common antenna for both transmitting and receiving, monostatic (single-site) radar became practical, and bistatic radar became dormant. It was not until the early 1950s that interest revived.¹

Bistatic radar employs two separated sites. Figure 1a shows its usual form. A transmitter is placed at one site and the associated receiving equipment is placed at another; the receiving site is separated from the transmitting site. Detection is based upon target reflections received at the receiving site. The total propagation time and the elevation and azimuth angles measured at the receiver site provide target-location information. In addition to the usual forms of pulse radar waveforms, various continuous modes of transmission are readily used because the separation of transmitting and receiving sites provides isolation.

36-2

BISTATIC AND MULTISTATIC RADAR

It is also possible to employ a transmitter and receiver at both sites. Each site may receive target reflections of radiation from its own transmitter and from the other transmitter.

Passive bistatic receiving systems utilize two receiving sites. They detect only the targets that radiate electromagnetic energy. Detection is usually based upon reception of the radiated energy at both sites. Target-location information is derived from signal arrival-time differences and angular measurements made at one or both sites. Passive systems have application where the operation of a radar transmitter is undesirable. Because of similarities to bistatic and multistatic radars, passive systems will be included in this chapter.




Fig. 1 Bistatic and tristatic geometry: (a) plane defined by the transmitter, target, and receiver; (b) coordinate system (site at b is deleted for bistatic purposes).

When separate transmitting and receiving antennas are at a single site, as is common in many CW radars, the term *bistatic* is not used to describe such a system since the radar has the characteristics of a monostatic radar.

Multistatic radar employs more than two separated sites. Some multistatic configurations can be treated as combinations of several bistatic radars or of several monostatic radars, or as combinations of bistatic with multistatic radars. Emphasis will be placed on, but not limited to, multistatic systems that provide features not obtainable in bistatic or monostatic radar. These features are discussed in Sec. 36.4. For all multistatic radars the available location techniques are more powerful than those for bistatic radar.

One form of multistatic radar might use one transmitter site with two or more receiving sites. It is capable of locating targets by means of echo arrival-time data without the use of angular information.

Multistatic radar might also employ a transmitter at each site. An example is the combination of three range-only monostatic radars, sometimes called a trilateration radar.

BISTATIC

Passive version;
False target.
configur.
and data
that can
that can
requir

36.2 BIS

Data col
with mo
static de
and mul
from mo
between
complica

For ta
(Fig. 1b)
ranges r
based up
shifts. \dots

work; fo
A ran
tions sho
the rang
Hence, u
arrival-t
($t_1 - t_2$)
of propa
equation

36.3 BIS
COL

The bist

where P_r
 P_t
 G_r
 G_t
 σ
 D_r
 D_t
 $L_p(l)$
 $L_p(r)$
 L_r
 λ

This equ
 $G^2 = G_r G_t$
right side
where